

AI-500-080 Series FMU 2 Field Monitoring Unit

Overview

The FMU 2 AI-500-080 series of controllers provides a cost-effective, easy to integrate means of adding monitoring and control of communications and field I/O to any project. The 19-inch rack mounted device is capable of remotely switching NEMA 5-15 power outlets inside the ITS cabinets. It is designed for extreme temperature applications and has low power requirements, making it suitable for solar powered applications. The unit comes in a variety of configurations supporting all common communication methods.

Several configurations are available with combinations of Ethernet, Wi-Fi, and Cellular Modem. All units come with multiple digital inputs and outputs as well as analog inputs. An RS-232 interface port is standard on the units, with additional RS-232/485 optional.

The unit works in conjunction with the Glance Platform, providing optional connectivity to the cloud-based Glance solution. Simply plug in your IT equipment and connect the I/O to add monitoring and control to your equipment. Also available are interfaces to field components via serial and Ethernet connectivity, using both standard and custom protocols.



Features

- ✓ Low cost Internet connectivity solution
- ✓ 19 inch rack mount 1 U high
- ✓ Remotely switchable outlets
- ✓ Variety of connectivity options
- ✓ Compatible with Glance platform
- ✓ GPS enabled for self-locating and mobile position tracking
- ✓ Low power consumption
- ✓ Local data storage, supporting store and forward schemes when offline
- ✓ Real Time Clock supporting scheduling applications
- ✓ Integral battery back-up for power fail reporting

Call us today to get started at [678.830.2170](tel:678.830.2170) or email us at [sales@appinfoinc.com!](mailto:sales@appinfoinc.com)

Hardware Specification



AI - 500-080

Connectivity

Cell Modem *	Yes
Wi-Fi	Optional
Ethernet Port (10/100Base-T)	Yes
RS-232 Port	Yes
RS-485 Port or RS-232 Port	Optional

Industrial I/O

Analog Inputs	8 (4 x 120V AC, 4 x 24V DC)
Digital Inputs	8 (4 x 120V AC, 4 x 24V DC)
Digital Outputs	4 (2 x NO/NC 2A Relay, 2 x Open Collector)

Power

Outlets	NEMA 5-15 (4 x 120V, remotely switchable rated 15 amp total load)
---------	---

Miscellaneous

Operating Systems	µC/OS-II
GPS	Yes
Operating Temperature	-40°C to 80°C
Humidity	5-95% non-condensing
Dimensions	17.5" W x 1.75" H x 7.5" D
Mounting	19 inch rack mount 1U
Input Voltage	120V AC
Real Time Clock	Yes
Flash Disk	Yes
Battery Backup	Yes

Also suitable for...

Solar/battery powered	Yes
Scheduling	Yes

* Specify carrier at time of order

** Custom configurations available for volume orders

